# PORTABLE FRIDGE / FREEZERS

# ENGEL

**General Catalog** 

### A LEGEND IN RELIABILITY

Whatever YOUR NEEDS
There's an ENGEL for you.
WILDERNESS / MARINE / ON THE ROAD



SAW FUJI

# ENGEL CELEBRATES 50 YEARS AS THE LEADING PROVIDER OF PORTABLE FRIDGE-FREEZERS



The leading brand for the past 50 years, only ENGEL portable fridge-freezers guarantee to go anywhere.

Their reputation speaks for itself. ENGEL's commitment to continuous improvement means that the ENGEL of today is the most reliable, efficient and quietest on the market, full of features to ensure it is easier to use than ever before.

Exclusive built-in AC/DC compatibility with automatic voltage selection standard on most models.

Unique 'Sawafuji Swing Motor' is the world's most efficient AC/DC compressor and uses less power than any other portable fridge/freezer compressor. Thermostat control gives reliable, temperature control. Deep interior for convenient upright bottle storage. Vents that allow easy storage. Turbo cooling fan (standard on most models) that boosts performance in confined spaces. Convenient on/off power indicator. Fully generator compatible (Automatic voltage regulated only). Tough, solid casing for harsh conditions. Steel handles (most models) double as tie down points. Soft, rounded edges protect vehicle interiors. High density polyurethane walls provide the best insulation. Excellent resale value.





# **LITTLE ENGEL**

#### ENGEL MD14F (14 litre)













The ENGEL MD14F (14 litre) is a totally portable yet very powerful 12V fridge/freezer for cars, trucks and boats. Carry chilled drinks and perishables wherever you go.



-		
Capacity	14 LITRE (14x375ml cans)	
Internal Dimensions (mm)	H213 W348 D190	
<b>External Dimensions (mm)</b>	H398 W442 D284	
Net Weight	11.5 KG	
DC Power Consumption	Variable from 0.5 - 2.8 AMPS	
Power	12V DC Only	









#### ENGEL MHD13F-DM (13 litre)

Ever wondered how useful it would be if there is such a fridge that shows the set temperature as well as the actual temperature inside? Now with voices from users fully reflected, the long-beloved 13-liter ENGEL has added a new face to its line.

Capacity	13 LITRE
Internal Dimensions (mm)	H190 W348 D190
External Dimensions (mm)	H372 W442 D284
Net Weight	11.5 KG
DC Power Consumption	Variable from 0.5 - 3.0 AMPS
Power	12/24V DC



Digital Temperature Controller



# **ENGEL COMPACT**

#### ENGEL MT17F (15 litre)











Capacity	15 LITRE (21x375ml cans)
Internal Dimensions (mm)	H230 W290 D200
External Dimensions (mm)	H364 W549 D307
Net Weight	16 KG
DC Power Consumption	Variable from 0.5 - 2.5 AMPS
Power	230V AC. 12/24V DC

#### ENGEL MT27F (21 litre)











Capacity	21 LITRE (29x375ml cans)
Internal Dimensions (mm)	H320 W290 D200
External Dimensions (mm)	H465 W549 D307
Net Weight	15 KG
DC Power Consumption	Variable from 0.5 - 2.5 AMPS
Power	230V AC, 12/24V DC

# **ENGEL LEGENDS**

#### ENGEL MT35F (32 litre)





This mid sized model is perfect for family sedans, wagons and small 4WD vehicles. Now quieter with increased capacity, performance and efficiency and with its rugged steel casing

this unit is ideal for two or three people.

Capacity	32 LITRE (44x375ml cans)	
Internal Dimensions (mm)	H270 W380 D270	
External Dimensions (mm)	H408 W648 D364	
Net Weight	21 KG	
DC Power Consumption	Variable from 0.5 - 2.5 AMPS	
Power	230V AC, 12/24V DC	

#### ENGEL MT45F (42 litre)





The benchmark portable fridge-freezer that other manufacturers try to emulate. Their advertising always compares their product to the ENGEL 40litre. These comparisons are hollow! When any one of their products has been working in the field for 50 years or more then they can dare to compare! For simplicity, durability, longevity, economy of power consumption and outright strength of construction.

Capacity	42 LITRE (60x375ml cans)
Internal Dimensions (mm)	H370 W380 D270
External Dimensions (mm)	H508 W648 D364
Net Weight	24 KG
DC Power Consumption	Variable from 0.5 - 2.5 AMPS
Power	230V AC, 12/24V DC

ENGEL MT45F-S (Silver Type) (42 litre)

#### ENGEL MR040F (38 litre Plastic casing)









MR040F is perfect for weekends away and general use for those who don't require the legendary strong steel ENGEL casing. MR040F is built with quality ENGEL components including the famous Sawafuji Swing motor to ensure ongoing reliability and the light-weight body means MR040F is even easier to carry with you as you go.

Features include protective rubber corners and a reversible lid for your convenience.

Capacity	38LITRE (50x375ml cans)
Internal Dimensions (mm)	H360 W386 D266
<b>External Dimensions (mm)</b>	H471 W636 D396
Net Weight	22 KG
DC Power Consumption	Variable from 0.5 - 2.75 AMPS
Power	230V AC, 12/24V DC





# **ENGEL LARGE**

#### ENGEL MT60F (60 litre)

Despite this model's large capacity it is still light enough to carry. Great for group excursions, fishing trips and extended touring. Twin storage baskets offer very easy access. The ENGEL 60 litre is a must for all serious fishermen.

Capacity	60 LITRE (80x375ml cans)
Internal Dimensions (mm)	H310 W510 D390







#### ENGEL MT60F-C COMBI (57 litre)

ENGEL, No.1 portable fridge/freezer, introduces the ENGEL Combi 60, the first REAL portable fridge/freezer with the convenience of separate fridge (32 litre) and freezer (25 litre) compartments. The thermostatically controlled fan provides cool air from the freezer section to maintain accurate refrigerator temperature.

Fridge Capacity	32 LITRE
Freezer Capacity	25 LITRE
External Dimensions (mm)	H441 W790 D490
Net Weight	33 KG
DC Power Consumption	Variable from 0.5-4.2 AMPS
Power	230V AC, 12/24V DC



#### ENGEL MT80F (80 litre)





ENGEL's BIG fridge/freezer gives you 33% more internal space than the MT60F with only a 120mm increase in height and no increase in power consumption.

Capacity	80 LITRE (118x375ml cans)
Internal Dimensions (mm)	H405 W510 D390
External Dimensions (mm)	H561 W790 D490
Net Weight	39 KG
DC Power Consumption	Variable from 0.5 - 4.2 AMPS
Power	30V AC, 12/24V DC



#### ENGEL MT80F-C COMBI (75 litre)

Following on from the overwhelming success of the MT60F - Combi, this model gives over 30% extra internal space with no power consumption increase.









	Fridge Capacity	42 LITRE
	Freezer Capacity	33 LITRE
	External Dimensions (mm)	H561 W790 D490
	Net Weight	40 KG
	DC Power Consumption	Variable from 0.5 - 4.2 AMPS
	Power	230V AC, 12/24V DC



# **ENGEL BUILT-IN** (for Camping & Boats)

Upright ENGEL refrigerators with the versatility to use in boats, caravans, four wheel drives, motorhomes, campervans, camper trailers, trucks and all types of mobile accommodation.

No more filling of gas bottles and having the inconvenience of running out of gas. These models also use the energy efficient Sawafuji Swing Motor.



Automatic temperature control make these a breeze to use. Features such as adjustable shelves and door pockets make these an ideal addition to any vehicle. Equipped with ice making compartment.

#### SB47F (40 litre built in, DC12/24V only)











Teak Panel

White Panel

Capacity	40 LITRE
Built-in Dimensions (mm)	H519 W386 D449
External Dimensions (mm)	H530 W423 D511
Net Weight	18 KG
DC Power Consumption	Variable from 0.5-2.5 AMPS
Power	12/24V DC

**SR70F** (57 litre built in)













Teak Panel

Capacity	57 LITRE
Built-in Dimensions (mm)	H520 W468 D524
External Dimensions (mm)	H530 W506 D586
Net Weight	20.2 KG
DC Power Consumption	Variable from 0.5-2.5 AMPS
Power	230V AC, 12/24V DC

#### **ENGEL FREE-STANDING**

**ST90F** (80 litre free standing)











Large capacity, built-in or free-standing fridges that incorporate a separate freezing compartment. Cleverly designed to fit into confined spaces in caravans and boats.

\*Available Accessory: Built-in Frame Kit

Capacity	80 LITRE
<b>External Dimensions (mm)</b>	H781 W528 D570
Net Weight	28 KG
DC Power Consumption	Variable from 0.5-2.6 AMPS
Power	230V AC, 12/24V DC



#### MB40V (40 Litre Built In, DC12/24V only)







This new built in model was designed for mounting concealed under a bench of a motor home or possibly in the galley of a boat.

The compressor can be mounted hanging from the bottom of the cabinet or remotely mounted up to a metre away from the cabinet.

Features Simply dial control, and LED interior light. Comes Standard with a small hanging basket.



Capacity	40 LITRE
External Dimensions (mm)	H635 W500 D340
Net Weight	20 KG
DC Power Consumption	Variable from 0.5-3.0 AMPS
Power	DC12/24V



Mode   Medical   Ministry   Mi					JF1	ECIFICATIO	/N					
Stock	Туре			MD44E	MUDAOS DI	NT475	MEGZE		MTOSE	MTOFF	NAT-455	NAT 4 SEC.
Description				MD14F	MHD13F-DM	MT17F	MT27F	MR040F	MT35F	MT35F-S	MT45F	MT45F-8
Section   Sec	Model								88 88	-	N to th	
	Storago volumo		Liter	14	13	15	21	38	32	32	42	42
Door of Lab	Storage volume		Cu. Ft.	0.49	0.46	0.53	0.74	1.34	1.13	1.13	1.48	1.48
Processive   Pr	Color	Case or Flange		Light Gray	Light Gray	Light Gray	Light Gray	Light Gray	Light Gray	Silver	Light Gray	Silver
Month   Profession   Profess		Door or Lid		Dark Gray	Dark Gray	Dark Gray	Dark Gray	Dark Gray	Dark Gray	Silver	Dark Gray	Silver
Depth   Depth   Perm   Depth   Sept   Depth   Depth		Height	mm	398	372	364	465	471	408	408	508	508
Mages   Mage	External Dimensions Wie	Width	mm	442	442	549	549	636	648	648	648	648
According   Acco		Depth			284							
Seal Annoy 10   Seal Annoy 1	Weight (Net)		-	11.5	11.5	16	15				24	24
Search Prescription   AC230Y   W	Rated Input Voltage							230(200~250), 50/60Hz				
Passad Amperiography   Cacy   A   Cacy   1.5   1.2   1.2   1.4   1.5   1.5   1.25   1.3   1.25   1.3   1.25	Rated Power Consumption											
March   Mar	Rated Amperage											
Receive   Pressure	rated Power Consumption											
New   Process	Cooling (heating)											
Automatic ACIDC Interchangeable	Performance "					10	16	10	1	10	10	40
Memorable Door Pocket			_									
Features    Removable Door Pocket												
Prechargeable District Changes   Right of Let												
LED Thermometer Display			(Right or Left)									
LED Interior Light												
Digital Thermo Controller	eatures		.,									
Carrying Handle					•							
Basket				Shoulde	ring Belt	•	•	•	•	•	•	
Color   Case or Flange   Light Gray   Light Gray   Silver   Silv						•	•	•	•	•	•	•
Model		Case Material		Plastic	Plastic	Plastic	Plastic	Plastic	Steel	Steel	Steel	Steel
Color   Case or Flange   Light Gray   Light Gray   Silver   Silver	уре	1			Chest	Open			Bui	lt-in		Free Stand
Liter   60				MT60F	MT60F-C	MT80F-S	MT80F-C-S	MB40V	SB47F	SB70F	SR70F	ST90F-
Color   Case or Flange   Color   Col								I have		ALC: UNK	Selection 2	
Cu. Ft.   Cu. Ft.   Cu. Ft.   Feft. 17   F	Model			1	-	-	-1					
Case or Flange			Liter	60	Ref:32 Fre:25	80	Ref:42 Fre:33	40	40	57	57	80 (Fre: 9
Door or Lid   Dark Gray   Light Gray   Silver   Silver					Fre:25 Ref:1.13		Fre:33 Ref:1.48					(Fre: 9
Height   mm   441   441   561   561   635   530   530   530   530   530   530   530   781		Case or Flange		2.12	Fre:25 Ref:1.13 Fre:0.88	2.83	Fre:33 Ref:1.48 Fre:1.17	1.41	1.41	2.01	2.01	(Fre: 9
Width mm   790   790   790   790   500   423   506   506   528	Storage volume			2.12 Light Gray	Fre:25 Ref:1.13 Fre:0.88 Light Gray	2.83 Silver	Fre:33 Ref:1.48 Fre:1.17 Silver	1.41	1.41 Black	2.01 Black	2.01 Black	(Fre: 9 2.83 Black
Wildlife   Millife   Mil	Storage volume	Door or Lid	Cu. Ft.	2.12 Light Gray Dark Gray	Fre:25  Ref:1.13 Fre:0.88  Light Gray  Light Gray	2.83 Silver	Fre:33  Ref:1.48 Fre:1.17  Silver  Silver	1.41	1.41  Black  Teak or White	2.01 Black Black	2.01  Black  Teak or White	(Fre: 9 2.83 Black Black
Regist (Net)	Storage volume Color	Door or Lid Height	Cu. Ft.	2.12 Light Gray Dark Gray 441	Fre:25 Ref:1.13 Fre:0.88 Light Gray Light Gray 441	2.83 Silver Silver 561	Fre:33  Ref:1.48 Fre:1.17  Silver  Silver  561	1.41	1.41  Black  Teak or White  530	2.01  Black  Black  530	2.01  Black Teak or White  530	(Fre: 9 2.83 Black Black 781
AC	Storage volume  Color  External Dimensions	Door or Lid Height Width	Cu. Ft.	2.12 Light Gray Dark Gray 441	Fre:25 Ref:1.13 Fre:0.88 Light Gray Light Gray 441 790	2.83 Silver Silver 561 790	Fre:33  Ref:1.48 Fre:1.17  Silver  Silver  561  790	1.41  635 500	1.41 Black Teak or White 530 423	2.01  Black  Black  530  506	2.01  Black Teak or White 530 506	2.83  Black  Black  781
DC   V   12/24   12/24   12/24   12/24   12/24   14/2   1/2   1	Storage volume  Color  External Dimensions	Door or Lid Height Width	Cu. Ft.	2.12 Light Gray Dark Gray 441 790 490	Fre:25 Ref:1.13 Fre:0.88 Light Gray Light Gray 441 790 490	2.83 Silver Silver 561 790 490	Fre:33  Ref:1.48 Fre:1.17  Silver  Silver  561  790  490	1.41  635 500 340	1.41  Black Teak or White  530  423  511	2.01  Black  Black  530  506  586	2.01  Black Teak or White  530  506  586	2.83  Black Black 781  528
Accord   A	Storage volume  Color  External Dimensions	Door or Lid Height Width Depth	Cu. Ft.  mm  mm  kg	2.12 Light Gray Dark Gray 441 790 490	Fre:25 Ref:1.13 Fre:0.88 Light Gray Light Gray 441 790 490 33	2.83 Silver Silver 561 790 490 39	Fre:33  Ref:1.48 Fre:1.17  Silver  Silver  561  790  490	1.41  635 500 340	1.41  Black  Teak or White  530  423  511  18	2.01  Black  Black  530  506  586	2.01  Black Teak or White  530  506  586  20	2.83 Black Black 781 528 570
Colling Performance   Colling Performance	Storage volume  Color  External Dimensions  Weight (Net)	Door or Lid Height Width Depth AC	Cu. Ft.  mm  mm  Kg	2.12 Light Gray Dark Gray 441 790 490	Fre:25 Ref:1.13 Fre:0.88 Light Gray Light Gray 441 790 490 33 230(200~25	2.83 Silver Silver 561 790 490 39 50), 50/60Hz	Fre:33  Ref:1.48 Fre:1.17  Silver  Silver  561  790  490	1.41  635 500 340	1.41  Black  Teak or White  530  423  511  18	2.01  Black  Black  530  506  586  20	2.01  Black Teak or White  530  506  586  20	2.83 Black Black 781 528 570
DC24V	Storage volume  Color  External Dimensions  Weight (Net)  Rated Input Voltage	Door or Lid Height Width Depth AC DC	Cu. Ft.  mm  mm  Kg  V	2.12 Light Gray Dark Gray 441 790 490 33	Fre:25 Ref:1.13 Fre:0.88 Light Gray Light Gray 441 790 490 33 230(200~25	2.83 Silver Silver 561 790 490 39 50), 50/60Hz	Fre:33 Ref:1.48 Fre:1.17 Silver Silver 561 790 490 40	1.41  635 500 340	1.41  Black Teak or White  530  423  511  18	2.01  Black  Black  530  506  586  20	2.01  Black Teak or White  530  506  586  20  230(200-25	(Fre: \$ 2.83 Black Black 781 528 570 28 0), 50/60H
Rated Power Consumption   DC12V	Storage volume Color	Door or Lid Height Width Depth AC DC AC230V	Cu. Ft.  mm  mm  Kg  V  W	2.12 Light Gray Dark Gray 441 790 490 33	Fre:25 Ref:1.13 Fre:0.88 Light Gray Light Gray 441 790 490 33 230(200~25	2.83 Silver Silver 561 790 490 39 50), 50/60Hz /24	Fre:33 Ref:1.48 Fre:1.17 Silver Silver 561 790 490 40	1.41  635 500 340 20	1.41  Black Teak or White  530  423  511  18	2.01  Black Black 530  506  586  20	2.01  Black Teak or White 530 506 586 20 230(200-25	(Fre: § 2.83  Black  Black  781  528  570  28  0), 50/601
Refrigerator   Cooling Performance (by thermostat control)   Refrigerator   C   -18   -18   -18   -18   -15   Less than 0°C (Ice Room)	Storage volume  Color  External Dimensions  Weight (Net)  Rated Input Voltage  Rated Power Consumption	Door or Lid Height Width Depth  AC DC AC230V DC12V	Cu. Ft.  mm mm Kg V V W A	2.12 Light Gray Dark Gray 441 790 490 33	Fre:25 Ref:1.13 Fre:0.88 Light Gray Light Gray 441 790 490 33 230(200~25 12 66 4.2	2.83 Silver Silver 561 790 490 39 50), 50/60Hz /24 66 4.2	Fre:33 Ref:1.48 Fre:1.17 Silver Silver 561 790 490 40 66 4.2	1.41  635 500 340 20	1.41  Black Teak or White 530  423  511  18 2.5	2.01  Black  Black  530  506  586  20  12/24	2.01  Black Teak or White 530 506 586 20 230(200-25	(Fre: £ 2.83  Black  Black  781  528  570  28  0), 50/600
Freezer   °C   -18   -18   -18   -18   -15   Less than 0°C (Ice Room)	Storage volume  Color  External Dimensions  Weight (Net)  Rated Input Voltage  Rated Power Consumption  Rated Amperage	Door or Lid Height Width Depth AC DC AC230V DC12V DC24V	Cu. Ft.	2.12 Light Gray Dark Gray 441 790 490 33	Fre:25 Ref:1.13 Fre:0.88 Light Gray Light Gray 441 790 490 33 230(200~25 12 66 4.2 2.1	2.83 Silver Silver 561 790 490 39 50), 50/60Hz /24 66 4.2 2.1	Fre:33 Ref:1.48 Fre:1.17 Silver Silver 561 790 490 40  666 4.2 2.1	1.41  635 500 340 20 3 1.5	1.41  Black Teak or White  530  423  511  18  2.5  1.3	2.01  Black  Black  530  506  586  20  12/24  2.5  1.3	2.01  Black Teak or White  530  506  586  20  230(200-25)  42  2.5  1.3	(Fre: \$ 2.83  Black  Black  781  528  570  28  0), 50/600  48  2.6  1.3
Automatic AC/DC Interchangeable   •   •   •   •   •   •   •   •   •	Storage volume  Color  External Dimensions  Weight (Net)  Rated Input Voltage  Rated Power Consumption  Rated Amperage	Door or Lid Height Width Depth AC DC AC230V DC12V DC12V	Cu. Ft.  mm mm Kg V W A A AH	2.12 Light Gray Dark Gray 441 790 490 33	Fre:25 Ref:1.13 Fre:0.88 Light Gray Light Gray 441 790 490 33 230(200~25 12 66 4.2 2.1 0.5-4.2	2.83 Silver Silver 561 790 490 39 50), 50/60Hz /24 66 4.2 2.1 0.5-4.2	Fre:33 Ref:1.48 Fre:1.17 Silver Silver 561 790 490 40  666 4.2 2.1	1.41  635 500 340 20 3 1.5	1.41  Black Teak or White  530  423  511  18  2.5  1.3	2.01  Black  Black  530  506  586  20  12/24  2.5  1.3  0.5-2.5	2.01  Black Teak or White  530  506  586  20  230(200-25)  42  2.5  1.3	(Fre: \$ 2.83  Black  Black  781  528  570  28  0), 50/600  48  2.6  1.3
Interchangeable Door Panel	Storage volume  Color  External Dimensions  Weight (Net)  Rated Input Voltage  Rated Power Consumption  Rated Amperage  Rated Power Consumption  Cooling Porformance	Door or Lid Height Width Depth  AC DC AC230V DC12V DC24V DC12V Refrigerator	Cu. Ft.  mm mm Kg V W A A AH	2.12 Light Gray Dark Gray 441 790 490 33 66 4.2 2.1 0.5-4.2	Fre:25 Ref:1.13 Fre:0.88 Light Gray Light Gray 441 790 490 33 230(200~25 12 66 4.2 2.1 0.5-4.2	2.83 Silver Silver 561 790 490 39 50), 50/60Hz /24 66 4.2 2.1 0.5-4.2	Fre:33 Ref:1.48 Fre:1.17 Silver Silver 561 790 490 40 666 4.2 2.1 0.5-4.2	1.41  635 500 340 20 3 1.5 0.5-3.0	1.41  Black Teak or White  530  423  511  18  2.5  1.3	2.01  Black  Black  530  506  586  20  12/24  2.5  1.3  0.5-2.5  5°C	2.01  Black Teak or White 530 506 586 20 230(200-25 42 2.5 1.3 0.5-2.5	(Fre: \$ 2.83  Black  Black  781  528  570  28  0), 50/600  48  2.6  1.3
Removable Door Pocket	Storage volume  Color  External Dimensions  Weight (Net)  Rated Input Voltage  Rated Power Consumption  Rated Amperage  Rated Power Consumption	Door or Lid Height Width Depth  AC DC AC230V DC12V DC24V DC12V Refrigerator Freezer	Cu. Ft.  mm mm Kg V V W A A AH °C °C	2.12 Light Gray Dark Gray 441 790 490 33 66 4.2 2.1 0.5-4.2	Fre:25 Ref:.1.3 Fre:0.88 Light Gray Light Gray 441 790 490 33 230(200~25 12 66 4.2 2.1 0.5-4.2 7'	2.83 Silver Silver 561 790 490 39 50), 50/60Hz //24 66 4.2 2.1 0.5-4.2 °C -18	Fre:33 Ref:1.48 Fre:1.17 Silver Silver 561 790 490 40  66 4.2 2.1 0.5-4.2	1.41  635 500 340 20 3 1.5 0.5-3.0	1.41  Black Teak or White 530  423  511  18 2.5  1.3  0.5-2.5	2.01  Black  Black  530  506  586  20  12/24  2.5  1.3  0.5-2.5  5°C  Less than 0°t	2.01  Black Teak or White 530 506 586 20 230(200-25) 42 2.5 1.3 0.5-2.5  C (Ice Room)	(Fre: \$\) 2.83  Black  Black  781  528  570  28  0), 50/600  48  2.6  1.3  0.5-2.
Interchangeable Door Opening (Right or Left)	Storage volume  Color  External Dimensions  Weight (Net)  Rated Input Voltage  Rated Power Consumption  Rated Amperage  Rated Power Consumption	Door or Lid Height Width Depth  AC DC AC230V DC12V DC24V DC12V Refrigerator Freezer Automatic AC/DC Interch	Cu. Ft.  mm mm Kg V W A A AH °C °C angeable	2.12  Light Gray  Dark Gray  441  790  490  33  66  4.2  2.1  0.5-4.2  -18	Fre:25 Ref:.1.3 Fre:0.88 Light Gray Light Gray 441 790 490 33 230(200~25 12 66 4.2 2.1 0.5-4.2 7' -18	2.83 Silver Silver 561 790 490 39 50), 50/60Hz /24 66 4.2 2.1 0.5-4.2 °C -18	Fre:33 Ref:1.48 Fre:1.17 Silver Silver 561 790 490 40  66 4.2 2.1 0.5-4.2	1.41  635 500 340 20 3 1.5 0.5-3.0	1.41  Black Teak or White 530  423  511  18  2.5  1.3  0.5-2.5	2.01  Black  Black  530  506  586  20  12/24  2.5  1.3  0.5-2.5  5°C  Less than 0°C	2.01  Black Teak or White 530 506 586 20 230(200-25  42 2.5 1.3 0.5-2.5  C (Ice Room)	(Fre: \$\) 2.83  Black  Black  781  528  570  28  0), 50/60l  48  2.6  1.3  0.5-2.
LED Thermometer Display	Storage volume  Color  External Dimensions  Weight (Net)  Rated Input Voltage  Rated Power Consumption  Rated Amperage  Rated Power Consumption	Door or Lid Height Width Depth  AC DC AC230V DC12V DC24V DC12V Refrigerator Freezer Automatic AC/DC Interch Interchangeable Door Pa	Cu. Ft.  mm mm Kg V W A A AH °C °C angeable	2.12  Light Gray  Dark Gray  441  790  490  33  66  4.2  2.1  0.5-4.2  -18  •	Fre:25 Ref:.1.13 Fre:0.88 Light Gray Light Gray 441 790 490 33 230(200~25 66 4.2 2.1 0.5-4.2 7' -18 •	2.83  Silver  Silver  561  790  490  39  50), 50/60Hz  /24  66  4.2  2.1  0.5-4.2  °C  -18  •	Fre:33 Ref:1.48 Fre:1.17 Silver Silver 561 790 490 40  66 4.2 2.1 0.5-4.2	1.41 635 500 340 20 3 1.5 0.5-3.0 -15	1.41  Black Teak or White 530  423  511  18 2.5  1.3  0.5-2.5	2.01  Black  Black  530  506  586  20  12/24  2.5  1.3  0.5-2.5  5°C  Less than 0°C	2.01  Black Teak or White  530  506  586  20  230(200-25)  42  2.5  1.3  0.5-2.5  C (Ice Room)  •	(Fre: \$\) 2.83  Black  Black  781  528  570  28  0), 50/601  48  2.6  1.3  0.5-2.
LED Interior Light </td <td>Storage volume  Color  External Dimensions  Weight (Net)  Rated Input Voltage  Rated Power Consumption  Rated Amperage  Rated Power Consumption</td> <td>Door or Lid Height Width Depth  AC DC AC230V DC12V DC24V DC12V Refrigerator Freezer Automatic AC/DC Interch Interchangeable Door Pa Removable Door Pocket</td> <td>Cu. Ft.  mm mm Kg V W A A AH °C °C angeable</td> <td>2.12  Light Gray  Dark Gray  441  790  490  33  66  4.2  2.1  0.5-4.2  -18  •</td> <td>Fre:25 Ref:.13 Fre:0.88 Light Gray Light Gray 441 790 490 33 230(200~25 12 66 4.2 2.1 0.5-4.2 7' -18 •</td> <td>2.83  Silver  Silver  561  790  490  39  500, 50/60Hz  /24  66  4.2  2.1  0.5-4.2  **C  -18  •  </td> <td>Fre:33 Ref:1.48 Fre:1.17 Silver Silver 561 790 490 40  66 4.2 2.1 0.5-4.2</td> <td>1.41 635 500 340 20 3 1.5 0.5-3.0</td> <td>1.41  Black Teak or White 530  423  511  18   2.5  1.3  0.5-2.5</td> <td>2.01  Black  Black  530  506  586  20  12/24  2.5  1.3  0.5-2.5  5°C  Less than 0°C   •</td> <td>2.01  Black Teak or White 530 506 586 20 230(200-25  42 2.5 1.3 0.5-2.5  C (Ice Room)</td> <td>(Fre: \$\) 2.83  Black  Black  781  528  570  28  0), 50/600  48  2.6  1.3  0.5-2.</td>	Storage volume  Color  External Dimensions  Weight (Net)  Rated Input Voltage  Rated Power Consumption  Rated Amperage  Rated Power Consumption	Door or Lid Height Width Depth  AC DC AC230V DC12V DC24V DC12V Refrigerator Freezer Automatic AC/DC Interch Interchangeable Door Pa Removable Door Pocket	Cu. Ft.  mm mm Kg V W A A AH °C °C angeable	2.12  Light Gray  Dark Gray  441  790  490  33  66  4.2  2.1  0.5-4.2  -18  •	Fre:25 Ref:.13 Fre:0.88 Light Gray Light Gray 441 790 490 33 230(200~25 12 66 4.2 2.1 0.5-4.2 7' -18 •	2.83  Silver  Silver  561  790  490  39  500, 50/60Hz  /24  66  4.2  2.1  0.5-4.2  **C  -18  •	Fre:33 Ref:1.48 Fre:1.17 Silver Silver 561 790 490 40  66 4.2 2.1 0.5-4.2	1.41 635 500 340 20 3 1.5 0.5-3.0	1.41  Black Teak or White 530  423  511  18   2.5  1.3  0.5-2.5	2.01  Black  Black  530  506  586  20  12/24  2.5  1.3  0.5-2.5  5°C  Less than 0°C   •	2.01  Black Teak or White 530 506 586 20 230(200-25  42 2.5 1.3 0.5-2.5  C (Ice Room)	(Fre: \$\) 2.83  Black  Black  781  528  570  28  0), 50/600  48  2.6  1.3  0.5-2.
Digital Thermo Controller <td>Storage volume  Color  External Dimensions  Weight (Net)  Rated Input Voltage  Rated Power Consumption  Rated Amperage  Rated Power Consumption  Cooling Porformance</td> <td>Door or Lid Height Width Depth  AC DC AC230V DC12V DC24V DC12V Refrigerator Freezer Automatic AC/DC Interch Interchangeable Door Pocket Interchangeable Door Opening</td> <td>Cu. Ft.  mm mm Kg V W A A AH °C °C angeable nel</td> <td>2.12  Light Gray  Dark Gray  441  790  490  33  66  4.2  2.1  0.5-4.2  -18  •</td> <td>Fre:25 Ref:.13 Fre:0.88 Light Gray Light Gray 441 790 490 33 230(200~25 12 66 4.2 2.1 0.5-4.2 70 -18 •</td> <td>2.83  Silver  Silver  561  790  490  39  50), 50/60Hz  /24  66  4.2  2.1  0.5-4.2  *C  -18  •   </td> <td>Fre:33 Ref:1.48 Fre:1.17 Silver Silver 561 790 490 40  66 4.2 2.1 0.5-4.2  -18 •</td> <td>1.41 635 500 340 20 3 1.5 0.5-3.0</td> <td>1.41  Black Teak or White 530  423  511  18  2.5  1.3  0.5-2.5</td> <td>2.01  Black  Black  530  506  586  20  12/24  2.5  1.3  0.5-2.5  5°C  Less than 0°C  • •</td> <td>2.01  Black Teak or White 530 506 586 20 230(200-25  42 2.5 1.3 0.5-2.5  C (Ice Room)  • • •</td> <td>(Fre: \$\) 2.83  Black  Black  781  528  570  28  0), 50/60l  48  2.6  1.3  0.5-2.</td>	Storage volume  Color  External Dimensions  Weight (Net)  Rated Input Voltage  Rated Power Consumption  Rated Amperage  Rated Power Consumption  Cooling Porformance	Door or Lid Height Width Depth  AC DC AC230V DC12V DC24V DC12V Refrigerator Freezer Automatic AC/DC Interch Interchangeable Door Pocket Interchangeable Door Opening	Cu. Ft.  mm mm Kg V W A A AH °C °C angeable nel	2.12  Light Gray  Dark Gray  441  790  490  33  66  4.2  2.1  0.5-4.2  -18  •	Fre:25 Ref:.13 Fre:0.88 Light Gray Light Gray 441 790 490 33 230(200~25 12 66 4.2 2.1 0.5-4.2 70 -18 •	2.83  Silver  Silver  561  790  490  39  50), 50/60Hz  /24  66  4.2  2.1  0.5-4.2  *C  -18  •	Fre:33 Ref:1.48 Fre:1.17 Silver Silver 561 790 490 40  66 4.2 2.1 0.5-4.2  -18 •	1.41 635 500 340 20 3 1.5 0.5-3.0	1.41  Black Teak or White 530  423  511  18  2.5  1.3  0.5-2.5	2.01  Black  Black  530  506  586  20  12/24  2.5  1.3  0.5-2.5  5°C  Less than 0°C  • •	2.01  Black Teak or White 530 506 586 20 230(200-25  42 2.5 1.3 0.5-2.5  C (Ice Room)  • • •	(Fre: \$\) 2.83  Black  Black  781  528  570  28  0), 50/60l  48  2.6  1.3  0.5-2.
Carrying Handle         •         •         •   -	Storage volume  Color  External Dimensions  Weight (Net)  Rated Input Voltage  Rated Power Consumption  Rated Amperage  Rated Power Consumption  Cooling Performance (by thermostat control)	Door or Lid Height Width Depth  AC DC AC230V DC12V DC24V DC12V Refrigerator Freezer Automatic AC/DC Interch Interchangeable Door Pa Removable Door Pocket Interchangeable Door Opening LED Thermometer Displa	Cu. Ft.  mm mm Kg V W A A AH °C °C angeable nel	2.12 Light Gray Dark Gray 441 790 490 33 66 4.2 2.1 0.5-4.2 -18 •	Fre:25 Ref:.13 Fre:0.88 Light Gray Light Gray 441 790 490 33 230(200~25 12 66 4.2 2.1 0.5-4.2 7' -18 •	2.83  Silver  Silver  561  790  490  39  50), 50/60Hz  /24  66  4.2  2.1  0.5-4.2  °C  -18  •    •	Fre:33 Ref:1.48 Fre:1.17 Silver Silver 561 790 490 40  66 4.2 2.1 0.5-4.2	1.41 635 500 340 20 15	1.41  Black Teak or White 530  423  511  18 2.5  1.3  0.5-2.5	2.01  Black  Black  530  506  586  20  12/24  2.5  1.3  0.5-2.5  5°C  Less than 0°t  •  •	2.01  Black Teak or White 530 506 586 20 230(200-25  42 2.5 1.3 0.5-2.5  C (Ice Room)  • • • •	(Fre: \$\) 2.83  Black  Black  781  528  570  28  0), 50/600  48  2.6  1.3  0.5-2.
Basket • • • • •	Storage volume  Color  External Dimensions  Weight (Net)  Rated Input Voltage  Rated Power Consumption  Rated Amperage  Rated Power Consumption  Cooling Performance (by thermostat control)	Door or Lid Height Width Depth  AC DC AC230V DC12V DC24V DC12V Refrigerator Freezer Automatic AC/DC Interch Interchangeable Door Packet Interchangeable Door Opening LED Thermometer Displa	Cu. Ft.  mm mm Kg V V W A A AH °C °C angeable nel  (Right or Left)	2.12 Light Gray Dark Gray 441 790 490 33 66 4.2 2.1 0.5-4.2 -18 •	Fre:25 Ref:.13 Fre:0.88 Light Gray Light Gray 441 790 490 33 230(200~25 12 66 4.2 2.1 0.5-4.2 7' -18 • •	2.83  Silver  Silver  561  790  490  39  50), 50/60Hz  /24  66  4.2  2.1  0.5-4.2  °C  -18  •    •	Fre:33 Ref:1.48 Fre:1.17 Silver Silver 561 790 490 40  66 4.2 2.1 0.5-4.2	1.41 635 500 340 20 3 1.5 0.5-3.0 •	1.41  Black Teak or White 530  423  511  18 2.5  1.3  0.5-2.5	2.01  Black  Black  530  506  586  20  12/24  2.5  1.3  0.5-2.5  5°C  Less than 0°t  •  •	2.01  Black Teak or White 530 506 586 20 230(200-25  42 2.5 1.3 0.5-2.5  C (Ice Room)  • • • • •	(Fre: \$ 2.83\)  Black  Black  781  528  570  28  0), 50/600  48  2.6  1.3  0.5-2.
	Storage volume  Color  External Dimensions  Weight (Net)  Rated Input Voltage  Rated Power Consumption  Rated Amperage  Rated Power Consumption  Cooling Performance (by thermostat control)	Door or Lid Height Width Depth  AC DC AC230V DC12V DC24V DC12V Refrigerator Freezer Automatic AC/DC Interch Interchangeable Door Pa Removable Door Pocket Interchangeable Door Opening LED Thermometer Displa LED Interior Light Digital Thermo Controller	Cu. Ft.  mm mm Kg V V W A A AH °C °C angeable nel  (Right or Left)	2.12 Light Gray Dark Gray 441 790 490 33 66 4.2 2.1 0.5-4.2 -18	Fre:25 Ref:.13 Fre:0.88 Light Gray Light Gray 441 790 490 33 230(200~25 12 66 4.2 2.1 0.5-4.2 7' -18 •	2.83 Silver Silver 561 790 490 39 50), 50/60Hz /24 66 4.2 2.1 0.5-4.2 °C -18 • •	Fre:33 Ref:1.48 Fre:1.17 Silver Silver 561 790 490 40  66 4.2 2.1 0.5-4.2	1.41 635 500 340 20  3 1.5 0.5-3.0  -15 •	1.41  Black Teak or White  530  423  511  18   2.5  1.3  0.5-2.5	2.01  Black  Black  530  506  586  20  12/24  2.5  1.3  0.5-2.5  5°C  Less than 0°G  •  •	2.01  Black Teak or White 530 506 586 20 230(200-25  42 2.5 1.3 0.5-2.5  C (Ice Room)  • • •	(Fre: \$ 2.83\)  Black  Black  781  528  570  28  0), 50/600  48  2.6  1.3  0.5-2.
	Storage volume  Color  External Dimensions  Weight (Net)  Rated Input Voltage  Rated Power Consumption  Rated Amperage  Rated Power Consumption  Cooling Performance (by thermostat control)	Door or Lid Height Width Depth  AC DC AC230V DC12V DC12V Refrigerator Freezer Automatic AC/DC Interch Interchangeable Door Pa Removable Door Pocket Interchangeable Door Opening LED Thermometer Displa LED Interior Light Digital Thermo Controller Carrying Handle	Cu. Ft.  mm mm Kg V V W A A AH °C °C angeable nel  (Right or Left)	2.12 Light Gray Dark Gray 441 790 490 33 66 4.2 2.1 0.5-4.2 -18 • •	Fre:25 Ref:.13 Fre:0.88 Light Gray Light Gray 441 790 490 33 230(200~25 12 66 4.2 2.1 0.5-4.2 7' -18	2.83 Silver Silver 561 790 490 39 50), 50/60Hz /24 66 4.2 2.1 0.5-4.2 °C -18 • •	Fre:33 Ref:1.48 Fre:1.17 Silver Silver 561 790 490 40  66 4.2 2.1 0.5-4.2	1.41 635 500 340 20 3 1.5 0.5-3.0	1.41  Black Teak or White  530  423  511  18   2.5  1.3  0.5-2.5	2.01  Black  Black  530  506  586  20  12/24  2.5  1.3  0.5-2.5  5°C  Less than 0°G	2.01  Black Teak or White 530 506 586 20 230(200-25  42 2.5 1.3 0.5-2.5  C (Ice Room)  • • •	(Fre: \$ 2.83   Black   Black   Free   Free



# **SAWAFUJI ELECTRIC CO., LTD.**

3, Nittahayakawa-cho, Ota-City, Gunma 370-0344 JAPAN PHONE: +81-276-56-7139 FAX: +81-276-56-6075

URL: http://www.sawafuji.co.jp/





